

EXTRUDED ABS RODS

					ABS	
					● Natural/Ivory	
ø (mm)	Weight (kg/m)	Tolerance (mm)		Length (mm)	S	L
10	0.090	+0.10	+1.10	1000	●	
15	0.200	+0.10	+1.50	1000	●	
20	0.360	+0.10	+1.60	1000	●	
30	0.820	+0.10	+1.70	1000	●	
40	1.450	+0.10	+1.90	1000	●	
50	2.270	+0.10	+2.50	1000	●	
60	3.270	+0.10	+3.00	1000	●	
80	5.810	+0.10	+4.20	1000	●	
90	7.077	+0.20	+5.20	1000		●
100	9.070	+0.30	+5.30	1000	●	
120	12.650	+0.30	+5.30	1000	●	
150	19.800	+0.30	+5.30	1000	●	

S: Stocked Item L: Subject to a leadtime or MOQ

EXTRUDED ABS SHEETS

					ABS	
					● Natural/Ivory	
Thk (mm)	Weight (kg/ Sheet)	Tolerance (mm)	Width (mm)	Length (mm)	S	L
10	7.05	+0.3 / +2.60	610	1220	●	
20	14.100	+0.3 / +2.60	610	1220	●	
25	17.650	+0.3 / +2.60	610	1220	●	
30	21.150	+0.5 / +3.00	610	1220	●	
40	28.200	+0.5 / +5.00	610	1220	●	
50	35.250	+0.5 / +5.00	610	1220	●	