

EXTRUDED PET-P RODS

Arnite® PET-P		OmniAlite® TX LF	
● White	● Black	● Grey/Blue	

ø (mm)	Weight (kg/m)	Tolerance (mm)		Length (mm)			Arnite® PET-P		OmniAlite® TX LF	
							S	L	S	L
12	0.17					3000	●			
16	0.30					3000	●			
20	0.50	+0.2	+0.8			3000	●	●		●
25	0.80			1000	2000	3000	●		●	●
30	1.10	+0.2	+1	1000	2000	3000	●	●		●
35	1.40			1000	2000	3000	●		●	●
40	1.90	+0.2	+1.2	1000	2000	3000	●	●		●
45	2.90			1000	2000	3000	●		●	
50	2.84			1000	2000	3000	●	●		●
55	3.52	+0.3	+1.3	1000	2000	3000		●		●
60	4.20			1000	2000	3000	●	●		●
65	4.91			1000	2000	3000	●		●	
70	5.70	+0.3	+1.6	1000	2000	3000	●	●		●
75	6.39			1000	2000	3000		●		●
80	7.50	+0.4	+2	1000	2000	3000	●	●		●
90	9.50	+0.5	+2.2	1000	2000	3000	●		●	●
100	11.50	+0.6	+2.5	1000	2000	3000	●		●	
110	13.76	+0.7	+3	1000	2000	3000		●		●
120	16.60	+0.8	+3.5	1000	2000	3000	●		●	●
130	19.27			1000	2000	3000	●		●	
135	22.29	+0.9	+3.8	1000	2000	3000		●		
150	26.90	+1	+4.2	1000	2000	3000	●		●	
160	29.16	+1.1	+4.5	1000	2000	3000	●			
175	35.00	+1.2	+5	1000	2000	3000		●		
180	36.88			1000	2000	3000	●			
200	45.52	+1.2	+5.5	1000	1000	2000	●			



S: Stocked Item L: Subject to a leadtime or MOQ

RODS