

EXTRUDED PET-P RODS

							Arnite® PET-P				OmniAlite® TX LF	
							● White		● Black		● Grey/Blue	
O/D (mm)	Weight (kg/m)	Tolerance (mm)		Length (mm)			S	L	S	L	S	L
12	0.17					3000	●					
16	0.30					3000	●					
20	0.50	+0.2	+0.8			3000	●		●		●	
25	0.80			1000	2000	3000	●			●	●	
30	1.10	+0.2	+1	1000	2000	3000	●		●			●
35	1.40			1000	2000	3000	●			●		●
40	1.90	+0.2	+1.2	1000	2000	3000	●		●			●
45	2.90			1000	2000	3000	●			●		
50	2.84			1000	2000	3000	●		●		●	
55	3.52	+0.3	+1.3	1000	2000	3000	●			●		
60	4.20			1000	2000	3000	●		●		●	
65	4.91			1000	2000	3000		●		●		
70	5.70	+0.3	+1.6	1000	2000	3000	●		●		●	
75	6.39			1000	2000	3000		●		●		
80	7.50	+0.4	+2	1000	2000	3000	●		●		●	
90	9.50	+0.5	+2.2	1000	2000	3000		●		●		●
100	11.50	+0.6	+2.5	1000	2000	3000	●			●	●	
110	13.76	+0.7	+3	1000	2000	3000	●			●		
120	16.60	+0.8	+3.5	1000	2000	3000	●			●	●	
130	19.27			1000	2000	3000	●			●		
135	22.29	+0.9	+3.8	1000	2000	3000		●				
150	26.90	+1	+4.2	1000	2000	3000	●		●			●
160	29.16	+1.1	+4.5	1000	2000	3000	●					
175	35.00	+1.2	+5	1000	2000	3000		●				
180	36.88			1000	2000	3000	●					
200	45.52	+1.2	+5.5				●		●			

S: Stocked Item L: Subject to a leadtime or MOQ