

TORLON® ROD

					Torlon® 4203		Torlon® 4301	
					● Yellow Ochre		● Olive	
O/D (mm)	Weight (kg/ft)	Tolerance (mm)	Length (mm)		S	L	S	L
3.18	0.003	T	1220	2440		●		
3.99	0.005	T	1220	2440		●		
4.75	0.008	T	1220	2440		●		
5	0.009	T	1220	2440		●		
6.02	0.012	T	1220	2440		●		
6.35	0.014	T	1220	2440	●		●	
8	0.022	T	1220	2440		●		
9.5	0.031	T	1220	2440	●		●	
11.1	0.042	T	1220	2440		●		●
12.7	0.055	T	1220	2440	●		●	
15.88	0.086	T	1220	2440		●		●
19.05	0.124	T	1220	2440	●		●	
22.2	0.168	T	1220	2440		●		●
25.4	0.220	T	1220	2440	●		●	
31.75	0.343	T	1220	2440	●		●	
34.9	0.415	T	1220	2440		●		●
38.1	0.494	T	1220	2440	●		●	
44.45	0.673	T	1220	2440	●		●	
50.8	0.879	T	1220	2440	●		●	
57.15	1.112	T	1220	2440	●		●	
60.33	1.239	T	1220	2440		●		
63.5	1.373	T	1220	2440	●		●	
69.85	1.661	T	1220	2440		●		●
76.2	1.977	T	1220	2440		●		●
82.55	2.321	T	1220	2440		●		●
88.9	2.691	T	1220	2440		●		●
101.6	3.515	T	1220	2440		●		●
111.13	4.205	T	1220	2440		●		
114.3	4.449	T	1220	2440		●		
127	5.492	T	1220	2440		●		●
130.18	5.771	T	1220	2440		●		
138.43	6.526	T	1220	2440		●		
152.4	7.909	T	1220	2440		●		
193.68	12.773	T	1220	2440		●		
203.2	14.061	T	1220	2440		●		
257	22.522	T	1220	2440		●		●

S: Stocked Item L: Subject to a leadtime or MOQ

T: Tolerance. All sizes are suitable to finish machining to