

PCTFE RODS

					Ext PCTFE		Mid PCTFE	
					● Natural/ Light Grey		● Natural/ Light Grey	
ø (mm)	Weight (kg/m or pc)	Tolerance (mm)		Length (mm)	S	L	S	L
4	0.040	+0.80	+3.0	1000		●		
5	0.050	+0.80	+3.0	1000		●		
6	0.080	+0.80	+3.0	1000		●		
8	0.130	+0.80	+3.0	1000		●		
10	0.180	+0.80	+3.0	1000		●		
12	0.260	+0.80	+3.0	1000		●		
13	0.310	+0.80	+3.0	1000		●		
15	0.410	+0.80	+3.0	1000		●		
16	0.460	+1.0	+3.0	1000		●		
18	0.590	+1.0	+3.0	1000		●		
20	0.710	+1.0	+3.0	1000		●		
25	1.110	+1.0	+3.0	1000		●		
28	1.400	+1.0	+3.0	1000		●		
30	1.600	+1.0	+3.0	1000		●		
30	0.245	+1.0	+3.0	150				●
32	0.279	+1.0	+3.0	150				●
35	2.190	+1.0	+3.0	1000		●		
35	0.335	+1.0	+3.0	150				●
38	2.580	+1.0	+3.0	1000		●		
38	0.393	+1.0	+3.0	150				●
40	2.860	+1.0	+3.0	1000		●		
40	0.440	+1.0	+3.0	150				●
45	3.630	+1.0	+3.0	1000		●		
45	0.552	+1.0	+3.0	150				●
50	4.480	+1.0	+3.0	1000		●		
50	0.680	+1.0	+3.0	150				●
55	0.720	+1.0	+3.0	150				●
60	0.660	+1.0	+3.0	150				●
65	0.550	+1.0	+3.0	150				●
70	0.457	+1.0	+3.0	150				●

S: Stocked Item L: Subject to a leadtime or MOQ